# **TOOLS CONTENTS**

	SECTION	PAGES	2
	Tube Cutters	1-to 4	
	Tube Benders	5 to 14	
2 - 2 + 5 2 2 4 7	45° Flaring Tools	15 to 17	
	45° Double Flaring Tools	18	
	37° Flaring Tools	19 to 22	
	Flaring & Swaging Tools	23 to 25	
	Tubing Tool Kits	26 to 27	
	Testing & Service Tools	28 to 29	
	Ratchet Wrenches	30	
	Index	31	
	Tubing Tool Selector	32 to 33	

## **Tube Cutters - Metal Tubing**


For hard or soft copper, aluminum, brass, thin wall steel, stainless steel, monel, titanium and other tubing.

#### HI-DUTY® TUBE CUTTERS

#### For 1/8" to 1-1/8" and 1/4" to 1-5/8" O.D. tubing

Unique design eliminates spiraling. Makes clean, right-angle cuts with no burrs or chips to clog tubing. Both cutters include: rollers with flare cut-off groove, fold away reamer and spare cutting wheel. Rugged aluminum alloy body designed for handling ease. Finish: hand buffed high luster nickel-chrome plated body.

- \$ 151.00 FT-TC-1000 Hi-Duty® tube cutter for 1/8" to 1-1/8" (4 to 28 mm) O.D. tubing. Length 5". Wt. 6.5 oz.
- \$ 208.46 FT-312-FC Hi-Duty® tube cutter for 1/4" to 1-5/8 (7 to 41 mm) O.D. tubing. Length 5-1/2". Wt. 7.0 oz.
- \$ 185.15 FT-TC-1020 Combination tube constrictor and tube cutter for 1/8" to 1-1/8"(4 to 26 mm) O.D. tubing. Includes constrictor wheel for making brazed connections. Wt. 6.5 oz.
- \$ 233.77 FT-S75015 Replacement cutting wheel for soft copper aluminum brass and steel tubing (supplied with FT-TC-1000, FT-312-FC and FT-TC-1020).
- \$ 146.69 FT-S75046 Replacement cutting wheel for stainless steel, monel and hard temper copper tubing.
- \$ 37.85 FT-S76637 Replacement constrictor roller wheel. Conforms to Federal Specification GGG-C-771d, Type II, Class 1





ENCLOSED THRUST BEARING FEED Hardened tool steel thrust bearing feed.




FLARE CUT-OFF GROOVE Groove in rollers reduces tube loss when cracked flare is removed.



RETRACTABLE REAMER
Fold away hardened steel
reamer with turned cutting
edge removes inside burns
cleanly. Filing surface
removes outside burns.



SPARE CUTTING WHEEL Spare cutting wheel carried under retractable locking reamer.



FILL WITH SOLDER

Joint is ready for sweating when constricted tube contracts smaller tube. Can be used for crimping applications.

#### IMP® TUBE CUTTERS

#### For 1/8" to 5/8" and 3/16" to 7/8" O.D. tubing

- \$ 71.85 FT-TC-1050 For 1/8" to 5/8" (4 to 15 mm) O D, tubing. Requires only 1-1/4" swing radius (requires only 1-3/8" swing radius with 5/8" tube). Unique design eliminates spiraling. Repositioned rollers to bottom of tool allows for easier cutter engagement on tubing. Enclosed feed screw minimizes contamination, assuring continued smooth operation. Redesigned feed mechanism and new stainless steel rollers improves overall cutting action. New handle for better grip. Finish: hand buffed high luster nickel-chrome plated body. Length: 1-3/4". Wt. 2.5 oz.
- \$ 92.54 FT-S32633 Replacement cutting wheel
- \$ 106.15 FT-TC-2050 For 3/16" to 7/8" (5 to 22 mm) O.D. tubing. (Requires only 1-11/16" swing radius). Wt. 4.0 oz.
- \$ 233.77 FT-S75015 Replacement cutting wheel





## **Tube Cutters - Metal Tubing**

For hard or soft copper, aluminum, brass, thin wall steel, stainless steel, monel, titanium and other tubing.

#### "BIG-IMP"® TUBE CUTTER

#### For 3/8" to 1-1/8" (10 to 28mm) O.D. tubing

- \$ 143.15 FT-174-F Big capacity, small size. Designed for use in tight quarters where other cutters won't fit. Requires only 1-15/16" swing radius (2-1/4"swing radius with 1-1/8" tube). Perfect for instrument panels, control cabinets, refrigeration units, freezers, air-conditioning, heating units, machine tools, etc. Aluminum alloy body, black finish with brushed highlights. Length: 2-11/16". Wt. 5.0 oz.
- \$ 233,77 FT-S75015 Replacement cutting wheel for soft copper, aluminum, brass and steel tubing (supplied with cutter).
- \$ 146.69 FT-875046 Replacement cutting wheel for stainless steel, monel and hard temper copper tubing.



#### FT-174-F



#### JUNIOR TUBE CUTTER

#### For 1/8" to 3/4" (4 to 19mm) O.D. tubing

- \$ 81.38 FT-227-FA Exceptionally handy in close quarters only 3-1/2" overall length. Makes quick, clean, right-angle cuts without flattening tube. Enclosed feed mechanism. Satin finish. Wt. 5.0 oz.
- \$ 92.54 FT-S32633 Replacement cutting wheel. Conforms to Federal Specification GGG-C-771d, Type II, Class I

#### FT-227-FA



#### ADJUST-O-MATIC® TUBE CUTTERS

#### For 3/8" to 2-5/8" and 2" to 4-1/8" O.D. tubing.

Ratchet feed mechanism speeds up cutting operation - opens quickly to insert tubing, slides to cutting position instantly, fine feed adjustment for cutting action. Extra wide rollers with flare cut-off groove stabilize tubing. Spare cutting wheel included under handle cap. Enclosed screw - type feed mechanism; light weight aluminum alloy body.

- \$ 324.23 FT-206-FB Adjust-O-Matic® satin nickel finish chrome plated tube cutter for tubing from 3/8" to 2-5/8" (10 to 66mm) O.D. tubing. Length closed 7-3/4". Wt. 2.0 lbs.
- \$ 215.00 FT-S74761 Replacement cutting wheel
- \$ 642.15 FT-406-FA Adjust-O-Matic® for 2" to 4-1/8" (51 to 104mm)
  O.D. tubing Length closed 11-1/4". Wt. 3.5 lbs.
- \$ 65.69 FT-874833 Replacement cutting wheel. Conforms to Federal Specification GGG-C-771d, Type II, Class I.





#### FT-406-FA






RATCHET FEED
Ratchet release opens cutter
instantly to maximum size



Push on handle to slide cutting wheel to tubing. Rotate handle for fine adjustment.



FLARE CUT-OFF GROOVE Wide flare cut-off groove in rollers to accommodate flares on large size tubing.



SPARE CUTTING WHEEL Spare cutting wheel included in handle under snap-off cap

## **Tube Cutters - Metal Tubing**

For hard or soft copper, aluminum, brass, thin wall steel, stainless steel, monel, titanium and other tubing.


#### Sawing Vice

For 1/8" to 1-1/2" (4 to 38mm) O.D. tube or hose.

\$ 883.46 FT-384-FA Grips tube or hose securely for perfect right-angle cuts. Excellent for holding stainless steel tubing and wire braid hose when cutting with hacksaw. Quick clamp adjustment to tube size with instant tube release. Replaceable hardened steel hacksaw guides. No loose parts. Fastens on bench or clamps in vise.

Conforms to Federal Specification GGG-V-436d.

Size: 5" x 3-1/8" x 5-1/8". Wt. 2.5 lbs.







Press to release



## **Tube Cutters - Plastic & Rubber Hose**

For non-metal reinforced hose and tubing.

#### SNIMP® PLASTIC TUBE AND HOSE SHEAR

For 1/16" to 1/2" (1 to 13mm) O.D. hose\* or tubing.

\$ 40.71 FT-307-FP Compact shear is spring loaded for safety. Replacable hardened steel blade. Length: 2-7/8" Wt. 1.0 oz.

17.69 FT-S8115601 Replacement blade.

"Not for use with metal reinforced hose



For non-metal reinforced hose and tubing.

## PRODUCTION PLASTIC TUBE AND HOSE SHEAR

For 1/8" to 13/16" (4 to 20mm) O.D. hose\* or tubing.

- \$ 350,31 FT-327-FP Replaceable hardened steel blade. Can be bench or wall mounted for production, or carried in tool kit. Wt. 1 lb.
- 5 78.92 FT-877615 Replacement cutting blade.

\*Not for use with metal reinforced hose

#### FT-327-FP



## Tube Benders - Lever Type

For soft copper, aluminum, brass, steel, stainless steel and other metals.

#### LEVER-TYPE TUBE BENDERS


For 1/8" to 1" O.D. tubing.

FT-364-FHA Each tool bends one size. Open side type which slips over tube at any point. Makes smooth, tight radius bends up to 180" with minimum effort. No scoring or flattening of tubing. Calibrated to show angle of bend. Wide hook grips tubing securely.



Easy 90° start

#### FT-364-FHA-06



Style furnished for 1/4" through 1/2" O.D. tubing

#### Each tool bends only one size.

List Price		Catalog Number	Tube O.D.	Radius to Center of Tube (in.)	Weight Each (lbs.)	
\$	211.69	FT-364-FH-02	1/8"	3/8"	0.5 lbs.	
\$	211.69	FT-364-FH-03	3/16"	7/16"	0.5 lbs.	
\$	264.00	FT-364-FHA-04	1/4"	9/16"	1.0 lbs.	
\$	332.92	FT-364-FHA-05	5/16"	11/16"	1,01 lbs.	
\$	283.23	FT-364-FHA-06	3/8"	15/16"	1.75 lbs.	
\$	534.46	FT-364-FHA-07	7/16"	1-1/2"	3.5 lbs.	
\$	510.46	FT-364-FHA-08	1/2"	1-1/2"	3.5 lbs.	
\$	671.00	FT-364-FHA-10°	5/8"	2-1/4"	5.5 lbs.	
5	965.85	FT-364-FHA-12*	3/4"	3"	7.0 lbs.	
\$	1,244.77	FT-364-FHA-14*	7/8"	3"	10.5 lbs.	
\$	1,854.62	FT-364-FHA-16*	1"	3-1/2"	10.5 lbs.	

#### FT-364-FH-02



Style furnished for 1/8" and 3/16" O.D. tubing.


Conforms to Federal Specifications GGG-B-191a Type III, Class 2

#### FT-364-FHA-10



Style furnished for 5/8" and 3/4" O.D. tubing.

#### FT-364-FHA-14



Features telescopic handles for increased leverage.

Expandable style furnished for 7/8" and 1" O.D. tubing.

#### Metric Size Bending Tools

	List	Catalog	Tube O.D.	Radius to	a december	Weigh	it Each	
Price		Number	(mm)	(mm)	(in.)	kg.	lbs.	
\$	286.62	FT-364-FHAM-6mm	6mm	14.2 mm	9/16"	0.45 kg	1.0 lbs	
\$	357.85	FT-364-FHAM-8mm	8mm	17.5 mm	11/16"	0.45 kg.	1.0 lbs.	
\$	328.08	FT-364-FHAM-10mm	10mm	24.0 mm	15/16"	0.79 kg.	1.75 lbs	
5	627.15	FT-364-FHAM-12mm	12mm	38.1 mm	1-1/2"	1.6 kg.	3.5 lbs	


<sup>\*</sup>For bending annealed copper and aluminum tubing only.

## Tube Benders - Lever Type

For soft copper, aluminum, brass, steel, stainless steel and other metals.

#### SWIVEL HANDLE TUBE BENDERS

FT-364-FHB. Our newest lever type bender, the patented 364-FHB series has a swivel handle that can be repositioned midway through a bend when both handles begin to meet. This simple feature allows easy fabrication of bends up to 180° with reduced effort, better control and without the crossing of handles, typical of most other type benders.




#### FT-364-FHB-06

PATENTED

#### Each tool bends only one size.

List Price		Catalog Number	O.D. (in.)	Radius to Center of Tube (in.)	Weight Each (lbs.)	
S	300.31	FT-364-FHB-04	1/4"	9/16"	1.0 lbs	
\$	368.69	FT-364-FHB-05	5/16"	11/16"	1.0 lbs.	
\$	330.00	FT-364-FHB-06	3/8"	15/16"	1.75 lbs.	
S	584.23	FT-364-FHB-07	7/16"	1-1/2"	3.5 lbs.	
\$	548.38	FT-364-FHB-08	1/2"	1-1/2"	3.5 lbs.	



Style furnished for 1/4" through 1/2" O.D. tubing.

#### Metric Size Bending Tools

Ε	List	Catalog	Tube O.D.	Radius to Ce	nter of Tube	Weight Each		
Price		Number	(mm)	(mm)	(in.)	kg.	lbs.	
\$	291.15	FT-364-FHBM-6mm	6 mm	14.2 mm	9/16"	0.45 kg	1.0 lbs.	
\$	361.15	FT-364-FHBM-8mm	8 mm	17.5 mm	11/16"	0.45 kg.	1.0 lbs.	
\$	338.15	FT-364-FHBM-10mm	10 mm	24.0 mm	15/16"	0.79 kg	1.75 lbs.	
\$	649.08	FT-364-FHBM-12mm	12 mm	38.1 mm	1-1/2"	1.6 kg.	3.5 lbs.	

## **Tube Benders - Lever & Spring Type**

For bending soft copper, aluminum, brass, steel, stainless steel and other tubing.

## FT-564-FH and FT-564-FHT LEVER TYPE HEAVY DUTY TUBE BENDERS For 3/8" and 1/2" O.D. tubing.


- . Meets ANSI/ASME Boiler/Power requirements.
- · Vise mountable.
- · Prevents slippage and flattening.
- Fully adjustable to compensate for variances in tube tolerance.
- . Starts with handles at 90" angle.
- . Built for rugged day-in and day-out use.
- · Precise bends!
- · Self aligning rollers eliminate scoring and reduce bending effort.

These heavy-duty tube benders feature high-strength tool steel construction on all components subjected to stress during the bending process-including forming rollers, form wheel, stop pins, hook, cam adjustment shaft. Unique offset handle design assures maximum power transfer between worker and bender. Bender will not "gyrate" as handles are brought to closed position.



#### FT-564-FH

PATENDED



List Price	Catalog Number	Tube O.D. (in.)	Bend Radius (in.) to Ctr. of Tube	Weight (lbs.) Each
\$ 1,473.62	FT-564-FHT-06	3/8"	15/16"	5 lbs.
\$ 1,473.62	FT-564-FH-06	3/8"	1-1/8"	5.5 lbs.
\$ 1,518.46	FT-564-FH-08	1/2"	1-1/2"	7 lbs.

## **Tube Benders - Lever & Spring Type**

For bending soft copper, aluminum, brass, steel, stainless steel and other tubing.

#### IMP® TRIPLE HEADER BENDERS

For soft copper, aluminum and thin wall steel tubing. For 1/8", 3/16", 1/4" and 3/16", 1/4", 5/16", 3/8" O.D. tubing.

Calibrated markings for making accurate left-hand, right-hand and offset bends. Ninety degree start requires less effort - making bending fast and easy. For soft copper aluminum and steel.

- \$ 141.08 FT-367-FH For 1/8", 3/16" and 1/4" (3,4, and 6 mm) O.D. tubing. 9/16" (14.2 mm) radius to center of tube. Wt. 0.5 lbs.
- 5 151.85 FT-368-FH For 3/16", 1/4", 5/16" and 3/8" (6 and 8 mm) O.D. tubing: 15/16" (17.5 mm) radius to center of tube. Wt. 1.0 lbs.



Bends 1/8" O.D. tube (FT-367-FH)




Bends 1/4" O.D. tube (FT-367-FH)



Bends 3/16" O.D. tube (FT-367-FH)



FT-368-FH



#### SPRING TYPE TUBE BENDERS

For soft copper and aluminum tubing. For 1/4" to 7/8" O.D. tubing.

Tools allow hand bending of soft tubing to any shape without collapsing walls.

Special spring steel, chrome finish. End belled for quick tube removal.

List Price		Catalog Number	Tube O.D. (in.)	Length (in.)	Weight (oz.)	
\$	15.00	FT-102-F-04	1/4"	10"	3 oz.	
\$	15.00	FT-102-F-05	5/16"	10"	3 oz.	
\$	17.92	FT-102-F-06	3/8"	10"	4 oz.	
\$	19.77	FT-102-F-07	7/16"	12"	6.25 oz	
5	19.77	FT-102-F-08	1/2"	12"	6.5 oz	
\$	20.38	FT-102-F-10	5/8"	12"	8 oz.	
\$	24.38	FT-102-F-12	3/4"	12"	10 oz.	
\$	25.54	FT-102-F-14	7/8"	12"	10 oz.	

FT-102-F



- \$ 134.23 FT-201-F Set of 8 benders for 1/4", 5/16", 3/8", 7/16, 1/2", 5/8", 3/4" and 7/8" O.D. tubing.
- S 108.85 FT-101-F Set of 6 benders for 1/4", 5/16", 3/8", 7/16", 1/2" and 5/8" O.D. tubing.
- 8 88.48 FT-163-F Set of 4 benders for 1/4", 3/8", 1/2" and 3/8" O.D. tubing.
- \$ 45.92 FT-112-F Set of 3 benders for 1/4", 5/16" and 3/8" O.D. tubing.

## **Tube Benders - Lever Type**

For bending soft copper, aluminum, brass, steel, stainless steel and other metal tubing.

## WIDE RANGE TUBE BENDER KITS For 1/4" to 7/8" O.D. tubing.

Each tool quickly adapts to all sizes in its range by changing forming wheel and block. Telescopic handles reposition during bend for best leverage. Calibrations show precise bend angle. One piece benders furnished for 1/4" and 5/16" O.D. sizes. Furnished in tool case with space for other tools needed on the job.

#### \$ 3,531.97 FT-260-FHA for 7 sizes Wt. 23 lbs.

Tube O.D. (in.)	Radius to Ctr. of Tube (in.)
1/4"	9/16"
5/16"	11/16"
3/8"*	1-5/8"
1/2"*	1-5/8"
5/8"*	2-1/4"
3/4"*	3"
7/8"*	3"

#### \$ 2,609.32 FT-350-FHA for 6 sizes Wt. 20 lbs.

Tube O.D.	Radius to Ctr. of Tube (in.)
(111.)	Of Tube (III.)
1/4"	9/16"
5/16"	11/16"
3/8"*	1-5/8"
1/2"*	1-5/8"
5/8"*	2-1/4"
3/4"*	3"

#### \$ 1,948.15 FT-360-FHA for 4 sizes Wt. 20 lbs.

Tube O.D.	Radius to Ctr.
(in.)	of Tube (in.)
3/8"*	1-5/8"
1/2"*	1-5/8"
5/8"*	2-1/4"
3/4"*	3"

Conforms to Federal Specification GGG-B-191 Type III, Class 1.

#### FT-260-FHA




All wide range benders furnished in tool case with space for other tools.

<sup>\*</sup>Recommended for bending annealed copper and aluminum tubing only.

For aircraft grade stainless steel (MIL-T-6845) and all other metal tubing of bending temper.

#### FT-270-F GEAR TYPE TUBE BENDER For 3/8" to 1-1/8" O.D. tubing.

For all bending work. Spur-gear type with 10-to-1 ratio for easy bending of all tempered tubing. Floating shoe aligns tube perfectly on calibrated forming wheel. Pull-pin on wheel speeds repositioning for bends over 90°. Portable. Can be hand held, clamped in vise or bolted to bench. Adapts to pipe vise with handle FT-271-F.




FT-271-F Pipe vise extension (fits all FT-270-F Benders). For use when clamping bender in pipe vise. Wt. 1.75 lbs.


#### Each tool bends only one size.

List Price		Catalog Number	O.D. (in.)	Radius from Ctr. to Ctr. of Tube (in.)	Min. Return from Ctr. to Ctr. of Tubing (in.)	Weight Each (lbs.)	Wall Thickness (in.)
\$	707.69	FT-270-F-06	3/8"	1-3/4"	4-1/2"	3 lbs.	.030" to .060"
\$	884.46	FT-270-F-08	1/2"	2-1/2"	6"	4.75 lbs.	.035" to .065"
\$	1,179.38	FT-270-F-10	5/8"	3"	7-1/2"	8,5 lbs.	.040" to .072"
S	1,383.54	FT-270-F-12	3/4"	4"	9-1/2"	15 lbs.	.042" to .083"
s	1,383.54	FT-270-F-14	7/8"	4"	9-1/2"	14.75 lbs.	.045" to .083"
S	1,383.54	FT-270-F-16	1"	4"	9-1/2"	14,75 lbs.	.065" to .095"
s	1,383.54	FT-270-F-18	1-1/8"	4"	9-1/2"	14.25 lbs.	.065" to .095"

For aircraft grade stainless steel (MIL-T-6845) and all other metal tubing of bending temper.

## REPLACEMENT PARTS For FT-270-F Gear Type Tube Benders





Order by Catalog Number and O.D. size. (See page 12 & 13 of FT 12/08 for List Price.) Each bender handles only one size.

Size	Catalog	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
(in.)	Number	Part No.	Part No.	Part No.												
3/8"	FT-270-F-06	FT-S62244	FT-S62245	FT-S62246	FT-S62247	FT-S62250	FT-S82251	FT-S62252	FT-S62253	FT-S62254	FT-S62255	FT-S62257	FT-S62258	FT-S 62838	FT-S62836	FT-S62839
1/2"	FT-270-F-08	FT-S62261	FT-S62264	FT-S62246	FT-S62263	FT-S62262	FT-S62260	FT-S82269	FT-S62253	FT-S62268	FT-S62255	FT-S62266	FT-S82265	FT-S 62840	FT-S62836	FT-S62839
5/8"	FT-270-F-10	FT-S62275	FT-S62280	FT-S62279	FT-S62278	FT-S62277	FT-S82276	FT-S62284	FT-S62285	FT-962283	FT-S62255	FT-S62281	FT-S62282	FT-S 62841	FT-S62836	FT-S62837
3/4"	FT-270-F-12	FT-S82305	FT-S82294	FT-S62298	FT-S62307	FT-S62306	FT-S62288	FT-S62292	FT-S62297	FT-S62291	FT-S62255	FT-S62296	FT-S62295	FT-S 62835	FT-S62836	FT-S62837
7/8"	FT-270-F-14	FT-S62302	FT-S82294	FT-S62298	FT-S62304	FT-S62303	FT-S62288	FT-S82292	FT-982297	FT-S62291	FT-S62255	FT-S62296	FT-S82295	FT-S 62835	FT-S62836	FT-S62837
198	FT-270-F-16	FT-582299	FT-S82294	FT-S62298	FT-S62301	FT-S62300	FT-S62288	FT-S62292	FT-S62297	FT-S62291	FT-S62255	FT-S62296	FT-S62295	FT-S62 835	FT-S62836	FT-S62837
1-1/8"	FT-270-F-18	FT-S62287	FT-S62294	FT-S62298	FT-S62290	FT-S62269	FT-S62288	FT-S62292	FT-S62297	FT-S62291	FT-S62255	FT-S62296	FT-S62295	FT-S62835	FT-S62836	FT-S62837

For aircraft grade stainless steel (MIL-T-6845) and all other metal tubing of bending temper.

## REPLACEMENT PARTS For FT-270-F Gear Type Tube Benders

List Price		Catalog Number	Tube Bender Size	
ş	707.69	FT-270-F-06	3/8" O.D. Gear Type Bender	
\$	344.15	FT-S62244	3/8" O.D. Gear Type Bender	
\$	38,85	FT-862245	3/8" O.D. Gear Type Bender	
\$	11.15	FT-S62246	3/8" O.D. Gear Type Bender	
5	72.54	FT-S62247	3/8" O.D. Gear Type Bender	
\$	92.77	FT-S62250	3/8" O.D. Gear Type Bender	
\$	285.31	FT-S62251	3/8" O.D. Gear Type Bender	
\$	72.54	FT-S62252	3/8" O.D. Gear Type Bender	
\$	6.69	FT-862253	3/8" O.D. Gear Type Bender	
\$	181.46	FT-S62254	3/8" O.D. Gear Type Bender	
\$	7.23	FT-S62255	3/8" O.D. Gear Type Bender	
\$	8.15	FT-S62257	3/8" O.D. Gear Type Bender	
\$	21.15	FT-S62258	3/8" O.D. Gear Type Bender	
\$	4.77	FT-S62836	3/8" O.D. Gear Type Bender	
\$	46.69	FT-S62838	3/8" O.D. Gear Type Bender	
\$	19.69	FT-S62839	3/8" O.D. Gear Type Bender	

List Price		Catalog Number	Tube Bender Size		
\$	1,179.38	FT-270-F-10	5/8" O.D. Gear Type Bender		
\$	7.23	FT-S62255	5/8" O.D. Gear Type Bender		
\$	674.15	FT-S62275	5/8" O.D. Gear Type Bender		
\$	542.62	FT-S62276	5/8" O.D. Gear Type Bender		
5	121.08	FT-S62277	5/8" O.D. Gear Type Bender		
\$	103.08	FT-S62278	5/8" O.D. Gear Type Bender		
\$	13.92	FT-S62279	5/8" O.D. Gear Type Bender		
\$	51.54	FT-S62280	5/8" O.D. Gear Type Bender		
\$	4.92	FT-S62281	5/8" O.D. Gear Type Bender		
\$	33,31	FT-S62282	5/8" O.D. Gear Type Bender		
S	228.31	FT-S62283	5/8" O.D. Gear Type Bender		
\$	92.77	FT-S62284	5/8" O.D. Gear Type Bender		
\$	6.62	FT-S62285	5/8" O.D. Gear Type Bender		
\$	4.77	FT-S62836	5/8" O.D. Gear Type Bender		
\$	18.15	FT-S62837	5/8" O.D. Gear Type Bender		
\$	63.46	FT-S62841	5/8" O.D. Gear Type Bender		

List		Catalog	Tube Bender		
	Price	Number	Size		
S	884.46	FT-270-F-08	1/2" O.D. Gear Type Bender		
\$	11.15	FT-S62246	1/2" O.D. Gear Type Bender		
\$	6.69	FT-S62253	1/2" O.D. Gear Type Bender		
\$	7.23	FT-S62255	1/2" O.D. Gear Type Bender		
\$	325.69	FT-S62260	1/2" O.D. Gear Type Bender		
\$	496.46	FT-S62261	1/2" O.D. Gear Type Bender		
5	109.15	FT-S62262	1/2" O.D. Gear Type Bender		
\$	73.31	FT-S62263	1/2" O.D. Gear Type Bender		
\$	55.46	FT-S62264	1/2" O.D. Gear Type Bender		
\$	27.85	FT-S62265	1/2" O.D. Gear Type Bender		
\$	8.15	FT-862266	1/2" O.D. Gear Type Bender		
\$	198.54	FT-S62268	1/2" O.D. Gear Type Bender		
S	91.00	FT-S62269	1/2" O.D. Gear Type Bender		
S	4.77	FT-S62836	1/2" O.D. Gear Type Bender		
\$	19.69	FT-S62839	1/2" O.D. Gear Type Bender		
S	45.38	FT-S62840	1/2" O.D. Gear Type Bender		

	List	Catalog	Tube Bender
	Price	Number	Size
\$	1,383.54	FT-270-F-12	3/4" O.D. Gear Type Bender
\$	7.23	FT-S62255	3/4" O.D. Gear Type Bender
\$	547.23	FT-S62288	3/4" O.D. Gear Type Bender
\$	262.69	FT-S62291	3/4" O.D. Gear Type Bender
\$	91.00	FT-S62292	3/4" O.D. Gear Type Bender
\$	91.00	FT-S62294	3/4" O.D. Gear Type Bender
\$	42.46	FT-S62295	3/4" O.D. Gear Type Bender
\$	5.15	FT-S62296	3/4" O.D. Gear Type Bender
\$	14.31	FT-S62297	3/4" O.D. Gear Type Bender
\$	24.23	FT-S62298	3/4" O.D. Gear Type Bender
\$	862.23	FT-S62305	3/4" O.D. Gear Type Bender
\$	145.46	FT-S62306	3/4" O.D. Gear Type Bender
\$	127.23	FT-S62307	3/4" O.D. Gear Type Bender
\$	63,46	FT-S62835	3/4" O.D. Gear Type Bender
\$	4.77	FT-S62836	3/4" O.D. Gear Type Bender
5	18.15	FT-S62837	3/4" O.D. Gear Type Bender

For aircraft grade stainless steel (MIL-T-6845) and all other metal tubing of bending temper.

## REPLACEMENT PARTS For FT-270-F Gear Type Tube Benders

List Price		Catalog Number	Tube Bender Size	
S	1,383.54	FT-270-F-14	7/8" O.D. Gear Type Bender	
\$	7.23	FT-S62255	7/8" O.D. Gear Type Bender	
\$	547.23	FT-S62288	7/8" O.D. Gear Type Bender	
S	262.69	FT-S62291	7/8" O.D. Gear Type Bender	
\$	91.00	FT-S62292	7/8" O.D. Gear Type Bender	
\$	91.00	FT-S62294	7/8" O.D. Gear Type Bender	
S	42.46	FT-S62295	7/8" O.D. Gear Type Bender	
S	5.15	FT-S62296	7/8" O.D. Gear Type Bender	
\$	14.31	FT-S62297	7/8" O.D. Gear Type Bender	
S	24.23	FT-S62298	7/8" O.D. Gear Type Bender	
\$	862.23	FT-S62302	7/8" O.D. Gear Type Bender	
\$	163.69	FT-S62303	7/8" O.D. Gear Type Bender	
5	127.23	FT-S62304	7/8" O.D. Gear Type Bender	
S	64.36	FT-S62835	7/8" O.D. Gear Type Bender	
\$	4.77	FT-S62836	7/8" O.D. Gear Type Bender	
S	18.15	FT-S62837	7/8" O.D. Gear Type Bender	

	List Price	Catalog Number	Tube Bender Size
S	1,383.54	FT-270-F-18	1-1/8" O.D. Gear Type Bender
\$	7.23	FT-S62255	1-1/8" O.D. Gear Type Bender
\$	835.69	FT-S62287	1-1/8" O.D. Gear Type Bender
\$	547.23	FT-S62288	1-1/8" O.D. Gear Type Bender
\$	163.70	FT-S62289	1-1/8" O.D. Gear Type Bender
\$	128.54	FT-S62290	1-1/8" O.D. Gear Type Bender
S	262.69	FT-S62291	1-1/8" O.D. Gear Type Bender
\$	91.00	FT-S62292	1-1/8" O.D. Gear Type Bender
\$	91.00	FT-S62294	1-1/8" O.D. Gear Type Bender
S	42.46	FT-S62295	1-1/8" O.D. Gear Type Bender
\$	5.15	FT-S62296	1-1/8" O.D. Gear Type Bender
\$	14.31	FT-S62297	1-1/8" O.D. Gear Type Bender
\$	24.23	FT-S62298	1-1/8" O.D. Gear Type Bender
\$	63.46	FT-S62835	1-1/8" O.D. Gear Type Bender
S	4.77	FT-S62836	1-1/8" O.D. Gear Type Bender
\$	18.15	FT-S62837	1-1/8" O.D. Gear Type Bender

	List	Catalog	Tube Bender
_	Price	Number	Size
\$	1,383.54	FT-270-F-16	1" O.D. Gear Type Bender
\$	7.23	FT-S62255	1" O.D. Gear Type Bender
S	547.23	FT-S62288	1" O.D. Gear Type Bender
\$	262.69	FT-S62291	1" O.D. Gear Type Bender
\$	91.00	FT-S62292	1" O.D. Gear Type Bender
S	91.00	FT-S62294	1" O.D. Gear Type Bender
s	42.46	FT-S62295	1" O.D. Gear Type Bender
S	5.15	FT-S62296	1" O.D. Gear Type Bender
5	14.31	FT-S62297	1" O.D. Gear Type Bender
\$	24.23	FT-S62298	1" O.D. Gear Type Bender
\$	870.31	FT-S62299	1" O.D. Gear Type Bender
S	163.69	FT-S62300	1" O.D. Gear Type Bender
S	127.23	FT-S62301	1" O.D. Gear Type Bender
\$	63.46	FT-S62835	1" O.D. Gear Type Bender
5	4.77	FT-S62836	1" O.D. Gear Type Bender
\$	18.15	FT-S62837	1" O.D. Gear Type Bender

For hard or soft copper, aluminum, brass, thin wall steel, stainless steel, monel, titanium and other metal tubing.

#### WORM GEAR TUBE BENDER

For 1/4", 5/16", 3/8", 1/2", 5/8", and 3/4" O.D. tubing.

\$ 9,465.15 FT-600-F Precision tool for highest quality work. Worm gear type with 50-to-1 ratio and crank with revolving hand grip. Keeps effort at a minimum. Follow bar eliminates drawing action and keeps tube in virtually perfect round. Adjustable pressure roller positions quickly in index holes. Enclosed gears. Furnished in carrying case.

Sizes of kit: 14" x 9" x 6". Wt. 35.0 lbs.

#### Tube Wall Thickness and Bend Radius

Tube O.D.	Wall Thickness	Radius to Ctr of Tube
(in.)	(in.)	(in.)
1/4"	.016" to .049"	3/4"
5/16"	.020" to .065"	1"
3/8"	.028" to .083"	1-1/4"
1/2"	.035" to .083"	2"
5/8"	.042" to .083"	2-1/2"
3/4"	.049" to .083"	3"

Conforms to Federal Specification GGGB-B-191b, Type I, Class 2 Meets ANSI specification (B31.1) and ASME Section III Nuclear Code.

#### FT-600-F



Furnished in carrying case.

#### GEAR TYPE TUBE BENDER

For 1/4", 5/16", 3/8", 1/2", 5/8", and 3/4" O.D. tubing.

\$ 37,257.92 FT-700-F Makes bends up to 180° in stainless steel tubing conforming to Specification MIL-T-6845. Precision construction maintains original diameter of tube within 5% at cross section of bend. Also bends copper, aluminum and other types of tubing. Size of kit 16" x 7" x 6-1/5". Wt. 32.0 lbs.


Calibration dial indicates angle on bend.

#### **Tubing Wall Thickness and Bend Radius**

Tube O.D. (in.)	Wall Thickness (in.)	Bend Radius Ctr of Tube (in.)
1/4"	.016" to .049"	9/16"
5/16"	.020" to .065"	11/16"
3/8"	.028" to .083"	15/16"
1/2"	035" to .083"	1-1/4"
5/8"	.042" to .083"	1-1/2"
3/4"	.049" to .083"	1-3/4"

(In some cases these wall thicknesses can be exceeded for copper and aluminum tubing. Consult factory.)

Conforms to Federal Specification GGB-B-191a, and Interim Amendment No. 2, Type I, Class I.




For soft tubing only - copper, aluminum, brass.

#### 45° FLARING TOOLS

For 3/16", 1/4", 5/16", 3/8", 7/16", 1/2" and 5/8" O.D. tubing.

- \$ 137.85 FT-296-FC Flares 7 sizes of tubing. Economical, fast operating tool. Quick slip-on, yoke. Easy operating swivel-type, hardened steel, chrome-finished cone assures smooth flares. Chrome and black finish. Wt. 1.75 lbs.
- \$ 176.08 FT-195-FC Flares 7 sizes of tubing. Rugged forged steel slip-on yoke and hardened flaring bar. Positive clamping action of bars prevents tube slippage. Self centering yoke with swivel-type, hardened steel chrome-finished flaring cone forms better flares with less effort. Design of yoke permits flaring where there is little space between nut and tube end. Satin finish nicket-chrome plated. Wt. 2.0 lbs.



#### 45° METRIC SIZE FLARING TOOL

\$ 231.08 FT-395-FAM Same as FT-195-FC except for metric size tubing 4mm, 6mm, 8mm, 10mm, 12mm, 15mm, 16mm O.D. tubing.



#### 45° LARGE SIZE FLARING TOOLS


Flares larger tube sizes. Quick slip-on yoke with hard chrome-finished, swivel flaring cone reduces effort. Positive clamping action of flaring bar eliminates tube movement. Nickel chrome finish.

Conforms to Federal Specification GGG-F-451a Type 1. Class 2. Style A.

- \$ 410.08 FT-375-FS For sizes 1/8", 3/16", 1/4", 5/16", 3/8", 7/16", 1/2", 5/8", and 3/4" O.D. tubing, Wt. 3.75 lbs.
- \$ 325.54 FT-376-FS For sizes 1/2", 5/8", 3/4" O.D. tubing, Wt. 2.0 lbs.
- \$ 499.00 FT-103-FS For sizes 3/4", 7/8", and 1" O.D. tubing, Wt. 3.75 lbs.
- \$ 521.92 FT-203-FA For sizes 5/8", 3/4", 7/8", and 1-1/8" O.D. tubing Wt. 3.75 lbs.

#### FT-103-FS

FT-195-FC / FT-395-FAM




For soft tubing only - copper, aluminum, brass.

#### HI-DUTY® FLARING TOOL

For 3/16", 1/4", 5/16", 3/8", 1/2" and 5/8' O.D. tubing.

\$ 322.77 FT-300-FB Hardened steel, chrome finished cone makes exceptionally smooth, high strength flares with a radius at base of flare - instead of sharp angle formed by ordinary tools. New slip-on yoke permits use in tight quarters, allows flaring where there is little space between nut and tube end. New feed screw design provides smoother, easier operation. Positive gripping and self-gauging of tube for exact flare size. Sliding die blocks lock in place by lever clamp action to ensure even dispersal of force around full diameter of tube for superior grip. Wt. 1.6 lbs.





SELF GAUGING-Just insert tube flush with top of die for accurate flare size.



FORMS STRONGER FLARES-Stronger flares assured by smooth, even radius formed at base of every flare by engineered chamfer.

#### 45° ROL-AIR® FLARING TOOL

Flares and burnishes 3/16", 1/4, 5/16", 3/8", 1/2", and 5/8" O.D. tubing.

\$ 358.77 FT-500-FC Faceted, hardened steel, chrome finished cone rolls out perfect 45° flares above die block, and automatically burnishes flare face reducing the need for deburring. Original wall thickness is maintained at base of flare. New slip-on yoke permits use in tight quarters, where there is little space between nut and tube end. Larger handle, with better leverage, and precision threads on feed screw make flaring effortless. Heat treated dies grip tubing without scoring. Satin chrome and black finish. Wt. 1.5 lbs.



Flares rolled out above die bar by super-smooth faceted cone. Makes stronger flares.



Unique detention mechanism for rapid engagement and release of die blocks.



#### METRIC SIZE 45° ROL-AIR® FLARING TOOL


\$ 350.69 FT-500-FCM Same ad FT-500-FC except for metric size tubing 6mm, 8mm, 10mm, 12mm, 15mm, and 16mm O.D.

For soft tubing only - copper, aluminum, brass.

#### "GRABBER"® ROL-AIR® 45° FLARING TOOL

Universal application. Adjustable opening holds all sizes. Flares and burnishes 3/16" to 5/8" (4.7 to 16mm) O.D. tubing.


FT-525-F Unique, self-adjusting, tube holding mechanism permits flaring any size tubing within the range of 3/16" to 5/8" (4.7 to 16mm) O.D. tubing. Innovative, single opening design is more compact and easier to use than conventional multi-opening flaring bars. Faceted, hardened steel, chrome finished cone rolls out and burnishes perfect 45° flare above the tube holding mechanism reducing need for deburring. Original wall thickness is maintained at base of flare. Slip-on self-centering yoke permits use in tight quarters. Large handle, with better leverage, and precision threads on feed screw make flaring effortless. High quality construction with satin chrome and black finish. Wt. 1.75 lbs.



FT-525-F



Flares rolled out above die bar by super-smooth faceted cone. Makes stronger flares.



- (1) Insert tubing into adjustable opening of tube holding assembly. Position end of tubing approximately 1/8" above the surface of holder.
- (2) Tighten clamp screw approximately 1/2 to 3/4 of a turn beyond free travel position to secure tubing.
- (3) Be certain flaring cone surface is ailed. Slip yoke over tube holding assembly centering on tubing. Twist yoke clockwise to lock in position. Turn yoke handle clockwise to flare.

## 45° Double Flaring Tools

For soft tubing only - steel, copper, aluminum, brass.

#### 45° DOUBLE FLARING TOOL

For 3/16", 1/4", 5/16", 3/8", and 1/2" O.D. tubing.

\$ 306.77 FT-93-FB Recommended for Bundy and other annealed soft steel tubing (wall thickness to .035"). Also makes single or double flares in soft copper or aluminum tubing. Small, light weight, easy to handle. Forged steel yoke; swivel-type hardened steel chrome-finished flaring cone. Bar provides positive grip of tubing. Includes tool case, Wt. 3.0 lbs.

Conforms to Federal Specification GGG-F-451a, Type 1, Class 2, Style A.



Screw down flaring cone with proper size adapter in tube. Retract cone remove adapter, complete flare.





SWIVEL-TYPE BALL
BEARING CONE
Ball thrust bearing in flaring

Ball thrust bearing in flaring cone minimizes friction, makes operation easier.




#### 45° DOUBLE FLARING TOOLS

For 1/4", 5/16", 3/8", 1/2", 5/8" and 3/4" O.D. tubing.

\$ 759.54 FT-195-FB Designed for automotive air-conditioning service. Makes double flares in soft copper or aluminum tubing (wall thickness to .035"). Easy operating ball bearing swivel-type hard chrome finished flaring cone. Quick slip-on yoke. Flaring bar offers positive grip of tubing. Also makes single flares. Wt. 5.6 lbs.



FT-93-FB





Screw down flaring cone with proper size adapter in tube. Retract cone remove adapter, complete flare.



SWIVEL-TYPE BALL BEARING CONE Ball thrust bearing in flaring cone minimizes friction, makes operation easier.




For soft, copper, aluminum and brass tubing.

#### 37° FLARING TOOL

For 3/16", 1/4", 5/16", 3/8", 1/2" and 5/8" O.D. tubing.

\$ 451.77 FT-437-FB For use with soft copper, aluminum and brass tubing. Hardened steel chrome finished cone makes exceptionally smooth, high strength flares with a radius at base of flare - instead of the sharp angle formed by ordinary tools. New slip-on yoke permits use in tight quarters, allows flaring where there is little space between nut and tube end. New feed screw design provides smooth, easier operation. Positive gripping and self-gauging of tube for exact flare size. Sliding die blocks lock in place by clamp action. Satin chrome and black finish. Wt. 1.75 lbs.



Forms Stronger Flares
Stronger flares assured by smooth,
even radius formed at base of every
flare by engineered chamfer.





#### 37° ROL-AIR® FLARING TOOL

For 3/16", 1/4", 5/16", 3/8", 1/2" and 5/8" O.D. tubing.

\$ 504.69 FT-507-FB For use with soft copper, aluminum and brass tubing.

Faceted, hard chrome finished cone rolls out perfect 37° flares above die block-then automatically burnishes flare face. Original wall thickness is maintained at base of flare. New slip-on yoke permits use in tight quarters where there is little space between nut and tube end. Larger handle, with better leverage, and precision threads on feed screw make flaring effortless. Heat treated dies firmly grip tubing. Satin chrome and black nickel finish.

Wt 1.75 lbs.



Flares rolled out above die bar by smooth facted cone. Makes stronger flares.

#### METRIC SIZE 37° ROL-AIR® FLARING TOOL

\$ 605.00 FT-507-FBM Metric 37" Rol-Air® flaring tool. Same as FT-507-FB except for metric size tubing 6mm, 8mm, 10mm, 12mm, 14mm, 15mm O.D. tubing.




For steel, stainless steel, copper, aluminum tubing.


#### 37° ROL-AIR® FLARING TOOLS

For 3/16", 1/4", 5/16", 3/8", 1/2" and 5/8" O.D. tubing.

- \$ 2,014.23 FT-400-F Forms 37° flares to Government Specifications in steel, stainless steel (including MIL-T-6845), titanium and other metal tubing. Positive stop gauge assures correct size of flare. Special burnishing action polishes flare face. Three rollers in flaring cone roll out 37° flare above die block. Roller action cuts effort required, maintains original wall thickness-eliminates stress concentration. Extension on yoke for clamping in vise. Satin chrome and black nickel finish. Furnished in sturdy tool case. Wt. 2.5 lbs.
- \$ 305.92 FT-401-FA Reaming yoke for 1/4" to 5/8" O.D. tubing. Recommended for use with steel and stainless steel tubing for proper flaring. Wt. 0.7 lbs.
- \$ 2,259.38 FT-402-FA Flaring and reaming kit. Contains No. FT-400-F Flaring Tool and No. FT-401-FA Reaming Yoke for 1/4" to 5/8" O.D. tubing. In tool case. Wt. 3.2 lbs.

Conforms to Federal Specification GGG-F-451a. Type 1, Class 1, Style A.





For steel, stainless steel, copper, aluminum tubing.

#### 37° HEAVY DUTY FLARING TOOL


For 1/8", 3/16", 1/4", 5/16", 3/8" and 1/2" O.D. tubing.

\$ 1,617.89 FT-447-F Forms 37° flares in annealed stainless steel (MIL-T-6345 or AMS5566), cold drawn stainless steel and annealed copper or aluminum tubing. Built to withstand continuous rugged service. Ball thrust bearing mechanism reduces effort required. Hardened tool steel die features non-slip grip of tubing, even after repetitive flaring. Bar has vise extension. Wt. 3.25 lbs.



Ball thrust bearing in flaring cone minimizes friction, makes operation easier

## FT-447-F



#### LARGE SIZE 37° ROL-AIR® FLARING TOOLS For 3/4", 7/8", 1", 1-1/4", 1-1/2" and 2" O.D. tubing.

Three cylinders in flaring cone roll out 37° flare above die block Flares soft steel, copper, aluminum and fully annealed stainless steel tubing. Roller action cuts effort required; maintains original wall thickness; eliminates stress concentration. Feed release and burnishing action. Vice clamp extension on yoke. Heat treated dies clamp tubing without marking it. Satin chrome and black nickel finish. Furnished in tool case.

- \$ 1,573.04 FT-537-F Flares and burnishes 3/4", 7/8", 1", and 1-1/4" O.D. tubing. Wt. 13.0 lbs.
- \$ 6,214.93 FT-637-F Flares and burnishes 1-1/4", 1-1/2", and 2" O.D. tubing. Wt. 13.0 lbs.


Feed release and burnishing mechanism.



Vise clamp extension



FT-537-F



Flares rolled out above die bar



For steel, stainless steel, copper, aluminum tubing.

#### 37° PRECISION FLARING TOOL

50.0 lbs.


For 1/8", 3/16", 1/4" 5/16", 3/8", 1/2", 5/8", 3/4", 1", 1-1/4" and 1-1/2" O.D. tubing,

\$ 32,263.54 FT-407-FA Precision tool flares (37\*) 1/8 hard
stainless steel and other tubing to extremely close tolerances.
Swivel-head clamp locks tubing in smooth bore die blocks. Lathe type tube feed. Flares rolled out by ball-bearing mounted concentric flaring cone. Tool must be clamped in vise. Will flare 1/8 hard stainless steel tubing in the sizes and wall thicknesses listed below in some cases these wall thicknesses can be exceeded when flaring aluminum copper or soft steel tubing. In tool case Wt.

Tube O.D. (in.)	Wall Thickness (in.)	Tube O.D. (in.)	Wall Thickness (in.)
1/8"	.020, .028	5/8"	.035, .049
3/16"	.010, .028	3/4"	.028, .035, .049
1/4"	.016, .028, .035	1"	.028, .035
5/16"	.035	1-1/4"	.035, .049
3/8"	.028, .035	1-1/2"	.035, .049, .065
1/2"	.035, .049		

Facing and Deburring Attachments. (Not included with FT-407-FA)

- \$ 52,094.00 FT-407-F Same as FT-407-FA, except includes the facing and deburring attachments.
- \$ 3,039.15 FT-S74460 Internal deburring tool for 1/8" to 1/2" O.D. tubing.
- \$ 7,437.77 FT-S74455 Internal deburring tool for 5/8" to 1-1/2" O.D. tubing.
- \$ 5,876.62 FT-S74447 External deburring tool.
- \$ 2,996.77 FT-S74462 Facing tool.





FT-407-F

## Flaring & Swaging Tools

Production and metric automotive flaring tools.

## PRODUCTION FLARING (45° & 37°) AND SWAGING TOOL For 3/16", 1/4", 5/16", 3/8", 1/2" and 5/8" O.D. tubing.

\$ 3,223.08 FT-555-FS Flares and swages 6 sizes of soft copper, aluminum or brass tubing. Makes both 45° and 37° single flares. Fast cam lever operation. Portable and vise or bench mountable. Change sizes quickly. Built in gauge for accurate flare size or swage depth. Unique jaws provide a positive non-slip grip on tubing. Wt. 6.5 lbs.



Swages 6 sizes



Makes 45° and 37° Flares



#### METRIC BUBBLE FLARING TOOL


For soft steel or Bundy tubing 4.75mm (3/16"), 6mm, 8mm or 10mm O.D. tubing.

\$ 378.38 FT-293-F Forms International Standard bubble flare in one fast operation. Fiares metric hydraulic brake lines used on European, Japanese and American automobiles and light trucks. This unique design makes flares on four sizes of tubing: 4.75mm (3/16"), 6mm, 8mm, and 10mm O.D. Will flare soft double wall steel tubing with a wall thickness up to .028". Can also be used with soft copper and aluminum tubing.

#### Replacement parts:

- \$ 33.08 FT-S8771801 4.75mm (3/16") adapten
- \$ 33.08 FT-S8771701 6mm adapter.
- \$ 33.08 FT-S8771601 8mm adapter.
- \$ 33.08 FT-S8771301 10mm adapter
- \$ 18.85 FT-S8694401 Wing nut.





FT-293-F

## Flaring & Swaging Tools

For soft tubing only - copper, aluminum, brass.

#### **PUNCH TYPE SWAGING TOOLS**


Use these tools for making tubing connections without fittings.

Enlarge end of tube, insert another tube of original O.D. size and solder together like a sweat fitting.

- \$ 60.51 FT-94-S Three-in-one swaging tool for 1/2", 5/8" and 7/8" O.D. tubing. Skin Packaged. Wt. 1.0 lbs.
- \$ 139.46 FT-193-S Vinyl case contains 4 swaging punches 1/4", 3/8", 1/2" and 5/8" O.D. tubing. Wt. 1.0 lbs.
- \$ 363.15 FT-195-SA Vise mountable flaring bar and 4 swaging punches 1/4", 3/8", 1/2" and 5/8" O.D. tubing. In tool case. Wt. 2.0 lbs.
- \$ 301.00 FT-S75531 Flaring bar only. Wt. 1.0 lb.

#### INDIVIDUAL SWAGING TOOLS

	List Price	Catalog Number	Tube O.D. (in.)	Weight (lbs.)
S	27.00	FT-93-S-03	3/16"	.20 lbs.
s	25.00	FT-93-S-04	1/4"	.20 lbs.
\$	31.15	FT-93-S-05	5/16"	.25 lbs.
\$	33.62	FT-93-S-06	3/8"	.25 lbs.
\$	36.15	FT-93-S-08	1/2"	.50 lbs.
\$	44.54	FT-93-S-10	5/8"	.50 lbs.
\$	46.77	FT-93-S-12	3/4"	.75 lbs.
\$	47.69	FT-93-S-14	7/8"	1.0 lbs.



FT-193-S





Enlarge end of tube, insert another tube, solder like a sweat fitting.



Tube height gauged by placing tubing even with bevel on swaging punch.

11

## Flaring & Swaging Tools

For soft tubing only - copper, aluminum, brass.

#### 45° SWAGING TOOL

For 1/2", 5/8" and 7/8" O.D. tubing.

\$ 397.92 FT-194-8 Screw-type swaging tool. Far easier to work with in close quarters than punch type tools. Perfect swaging alignment of tube every time. Hardened steel chrome finished adapters change quickly. In tool case. Wt. 2.0 lbs.

#### Replacement Parts:

- \$ 76.38 FT-278-FS-08 Adapter 1/2"
- \$ 76.38 FT-278-FS-10 Adapter 5/8"
- S 77.15 FT-278-FS-14 Adapter 7/8"

#### FLARING (45°) & SWAGING TOOLS

For 1/8" to 3/4" and 4mm to 22mm O.D. tubing.

S 637.85 FT-275-FS Flares and swages, Converts quickly. Screw-type feed. Ideal for use in close quarters. Two bars included cover 9 sizes. Swivel-type swaging adapters and flaring cone are hardened steel chromefinished for easy operation. Self-centering, slip-on forged steel yoke. In tool case. Wt. 3.5 lbs. Flares 1/8", 3/16" 1/4", 5/16" 3/8" 7/16", 1/2", 5/8", and 3/4" O.D. Includes 5 swage adapters for 3/16", 1/4" 5/16", 3/8", 1/2", 5/8", 3/4" O.D. tubing.

#### Replacement Parts:


- S 76.38 FT-278-FS-03X04X06 Adapter 3/16", 1/4", 3/8"
- \$ 76.38 FT-278-FS-05 Adapter 5/16"
- \$ 76.38 FT-278-FS-08 Adapter 1/2"
- S 76.38 FT-278-FS-10 Adapter 5/8"
- \$ 76.38 FT-278-FS-12 Adapter 3/4"
- \$ 50.46 FT-S38600 Flaring Cone

\$ 617.92 FT-275-FSM Metric flaring and swaging tool. Same as FT-275-FS except for metric size tubing 4mm, 6mm, 8mm, 10mm, 12mm, 14mm, 15mm, 18mm, 18mm, 22mm O.D. tubing. In tool case. Wt. 3.5 lbs.


#### Replacement Parts:

- \$ 76,38 FT-278-FSM4-6-10 Adapter 4mm, 6mm, 10mm
- \$ 76.38 FT-278-FSM-08 Adapter 8mm
- \$ 76.38 FT-278-FSM-12 Adapter 12mm
- \$ 76.38 FT-278-FSM-14 Adapter 14mm
- \$ 76.38 FT-278-FSM-15 Adapter 15mm

#### FT-194-S



#### FT-275-FS \ FT-275-FSM



- \$ 76.38 FT-278-FSM-16 Adapter 16mm
- \$ 76.38 FT-278-FSM-18 Adapter 18mm
- \$ 76.38 FT-278-FSM-22 Adapter 22mm
- \$ 50.46 FT-S38600 Flaring Cone


## **Tubing Tool Kits**

#### **CUTTING AND FLARING KITS**


Each kit contains No. FT-TC-1000 tube cutter for 1/8" to 1-1/8" O.D. tubing and a 45" or 37" flaring tool. In tool case,

	List Price	Catalog Number	Tube Cutter	Flaring Tool	Range of Flaring Tool	Wt. (lbs.)
5	315.23	FT-1226-FA	FT-TC-1000	FT-195-FC (45°)	3/16", 1/4", 5/16", 3/8", 7/16", 1/2", 5/8" O.D.	3.0 lbs
Ş	476.92	FT-123-FA	FT-TC-1000	FT-300-FB (45°)	3/16", 1/4", 5/16", 3/8", 1/2", 5/8" O.D	2.75 lbs
\$	552.23	FT-124-FA	FT-TC-1000	FT-500-FC (45° Rol-Air®)	3/16", 1/4", 5/16", 3/8", 1/2", 5/8" O.D.	2.75 lbs
5	617.92	FT-122-FA	FT-TC-1000	FT-437-FB (37°)	3/16", 1/4", 5/16", 3/8", 1/2", 5/8" O.D.	2.75 lbs
\$	498.38	FT-120-F	FT-TC-1000	FT-375-FS (45°)	1/8", 3/16", 1/4", 5/16", 3/8", 7/16", 1/2", 5/8", 3/4" O.D.	2.75 lbs

#### FT-1226-FA



### FT-124-FA



## **Tubing Tool Kits**

For flaring, cutting, and binding soft copper, aluminum, and brass tubing.


#### CUTTING FLARING AND SWAGING KIT For soft copper and aluminum tubing.

\$ 733.92 FT-275-FSC Kit contains a FT-TC-1000 tube cutter for 1/8" to 1-1/8" O.D. tubing and FT-275-FS flaring and swagging tool. In tool case. Wt. 3.0 lbs.

> Flares: 1/8", 3/16", 1/4", 5/16", 3/8", 7/16", 1/2", 5/8", and 3/4" O.D. tubing.

Swages: 3/16", 1/4", 5/16", 3/8", 1/2", 5/8", and 3/4" O.D. tubing.





In tool case

#### FlarePro® FOUR-IN-ONE FLARING & SWAGING TOOL

For copper, aluminum, steel, stainless steel and other metal tubing.

\$ 2,204.08 FT-2000-FS Individual size jaw sets are used for positive clamping compactness and operating convenience.

Socket head screws are provided for clamping the jaws to the yoke and feeding the tube forming components. The screws are hand turned for all free travel movement when advancing or retracting.

A hex socket and 3/8" square drive ratchet are furnished for easy operation of the threaded members under load. Tube forming components (flaring cones, double flaring adapters, and swaging adapters) are retained on the feedscrew by a ball detent mechanism and can be snapped on and off for quick change as required.

The tool is designed to permit hand held or vise mounted operation. Wt. 7.0 lbs.

#### Flaring - 37° and 45°

Flares soft copper, brass aluminum, steel and stainless steel in nine tube sizes: 1/8", 3/16", 1/4", 5/16", 3/8", 7/16", 1/2", 5/8", and 3/4" O.D. tubing.


#### Double Flaring - 45° Only

Double flares soft copper, aluminum and steel (Bundy or G.M. to .035 wall) in seven tube sizes, 3/16", 1/4", 5/16", 3/8", 1/2", 5/8", and 3/4" O.D. tubing.

#### Swaging

Swages soft copper, aluminum and brass in seven tube sizes: 3/16", 1/4", 5/16", 3/8", 1/2", 5/8", and 3/4" O.D. tubing.






## **Testing and Service Tools**

#### PINCH-OFF TOOL

For 1/4" to 1/2" O.D. tubing.

Temporarily closes soft copper, aluminum or steel tubing so no liquid or gas passes sealed part. Lets you disconnect line while making repairs without loss of liquid or gas. Also opens tubing to allow flow.

\$ 146.62 FT-105-FF Pinch-Off Tool for 1/4", 5/16", 3/8", and 1/2" O.D. tubing. Wt. .75 lbs.



#### INNER-OUTER REAMING AND DEBURRING TOOLS For 3/16" to 1/2" O.D. tubing.

Reams both inside and outside edges of tube with 3 hollow ground cutters. Tough die cast body. Deburrs both clockwise and counter clockwise. Fluted body is shaped to fit comfortably in palm.

- \$ 111.08 FT-208-F Reamer for copper, aluminum and brass tubing. Hardened steel cutter blades. Blue finish. Wt. 63 lbs.
- \$ 353.15 FT-208-FSS Reamer for aircraft grade stainless steel tubing; hard or soft copper. Aluminum, brass and steel tubing. Tungsten hardened tool steel cutter blades. Black finish. Wt. 63 lbs.







FT-208-FSS

#### **TUBING TEST PLUGS**

For 1/4" to 1-5/8" O.D. tubing.

For temporary shut-off of tubing without pinching it off or installing a valve. Especially handy for plumbing, heating, refrigeration and instrumentation when trouble shooting for leaks. Light weight, fast acting, dependable. Insert plug in tube end and tighten wing nut. Expander seals tube and holds pressures to 100 psi.

List Price		Catalog Number	Tube O.D. (in.)	Weight Each (oz.)	List Price		Replacement Sleeve	
\$	36.85	FT-140-F-04	1/4"	.5 oz.	\$	9.79	FT-S62641	
\$	40.46	FT-140-F-06	3/8"	.75 oz.	\$	11.69	FT-S62648	
\$	40.46	FT-140-F-08	1/2"	1.0 oz	\$	11.69	FT-S62655	
S	50.08	FT-140-F-10	5/8"	1.5 oz.	S	11.69	FT-S62661	
s	52.08	FT-140-F-12	3/4"	2.0 oz.	S	11.69	FT-S62666	
\$	75.69	FT-140-F-14	7/8"	3.0 oz	s	22.46	FT-S66434	
S	85.00	FT-140-F-18	1-1/8"	4.0 oz.	S	33.38	FT-S66435	
\$	175.77	FT-140-F-22	1-3/8"	4.0 oz.	S	28.05	FT-S71174	
5	177.31	FT-140-F-26	1-5/8"	5.0 oz.	5	34,69	FT-S71177	

FT-140-F-06 / FT-142-F



\$ 153.00 FT-142-F Test plug kit for 1/2", 5/8" and 7/8" O.D. tubing. Wt. 5 lbs.

## **Testing and Service Tools**

#### 45° REFACING TOOL

For 1/4", 5/16", 3/8", and 1/2" SAE 45° flare fittings.

\$ 902.00 FT-345-FA With cutter and adapters for 1/4", 5/16", 3/8", 1/2" and 5/8" fittings. Makes nicked or marred seats on brass and other nonferrous fittings and valves as good as new. Precision feed. Replaceable cutter. In tool case. Wt. 2.0 lbs.

#### Adapters:

- \$ 77.85 FT-346-F-04 1/4" O.D.
- S 82.08 FT-346-F-05 5/16" O.D.
- \$ 97.69 FT-346-F-06 3/8" O D
- 5 109.62 FT-346-F-08 1/2" O.D.
- S 105.15 FT-346-F-10 5/8" O.D.
- \$ 239.38 FT-S63412 Replacement Cutter

#### FT-345-FA



In tool case

### **Ratchet Wrenches**

For tube fittings, valves, nuts, bolts.

#### RATCHET WRENCHES

#### For Refrigeration and Air-Conditioning Service

- 55.46 FT-127-C Compressor access valve wrench. Chrome plated. Has 1/4", 3/8", 3/16", and 5/16" square drive ratchets and is specially designed for use on compressors with access valves
- in hard to reach places. Reversible ratchets.
- 56.46 FT-127-CO Same as FT-127-C except with unique 25" offset that provides additional convenience in hard to reach places.
- 139.43 FT-123-C Rugged steel forged wrench. For use on small refrigerant cylinders, shut-off valves, packing gland nuts, etc.
- FT-123-C Ratchet has 1/4" square drive and raised face. Handle has 3/16" and 1/4" square drives and 1/2" hex.
- 88.15 FT-124-C Combination wrench with the four sizes most needed for servicing air-conditioning and refrigerator equipment:
  - . 9/16" hex for dust cap on access valves and plug oil check on compressor
  - . 1/2" hex for compressor mounting bolts.
  - . 1/4" square for valve stem and service valves and old style compressor valves.
  - . 3/16" square for valve refrigerant charging tanks.
- 321.92 FT-125-C Rugged, steel forged wrench with four sizes covering almost any application. Ratchet has 1/4" drive on one end; other end has 3/16" and 5/16", square openings, plus 9/16" hex opening.



FT-125-C

FT-127-C

FT-127-CO



### **Parts Index**

FT-101-F8	FT-278-FSM-1425	FT-555-FS23	FT-S6230211,13
FT-102-F-048	FT-278-FSM-1525	FT-564-FH-067	FT-S6230311,13
FT-102-F-058	FT-278-FSM-1625	FT-564-FH-087	FT-S6230411,13
FT-102-F-068	FT-278-FSM-1825	FT-564-FHT-067	FT-S6230511,12
FT-102-F-078	FT-278-FSM-2225	FT-600-F14	FT-S6230611,12
FT-102-F-088	FT-278-FSM4-6-1025	FT-637-F21	FT-S6230711,12
FT-102-F-108	FT-293-F23	FT-700-F14	FT-S6264128
FT-102-F-128	FT-296-FC15	FT-93-FB18	FT-S6264828
FT-102-F-148	FT-300-FB16	FT-93-S-0324	FT-S6265528
FT-102-F-14 FT-103-FS15	FT-307-FP4	FT-93-S-0424	FT-S6266128
FT-105-FF28	FT-312-FC1	FT-93-S-0524	FT-S6266628
FT-112-F8 FT-120-F26	FT-327-FP4 FT-345-FA29	FT-93-S-0624	FT-S6283511,12,13
	FT-346-F-0429	FT-93-S-0824	FT-S6283611,12,13
FT-122-FA26		FT-93-S-1024	FT-S6283711,12,13
FT-1226-FA26	FT-346-F-0529	FT-93-S-1224	FT-S6283811,12
FT-123-C30	FT-346-F-0629	FT-93-S-1424	FT-S6283911,12
FT-123-FA26	FT-346-F-0829	FT-94-S24	FT-S6284011,12
FT-124-C30	FT-346-F-1029	FT-S326331,2	FT-S6284111,12
FT-124-FA26	FT-350-FHA9	FT-S3860025	FT-S6341229
FT-125-C30	FT-360-FHA9	FT-S6224411,12	FT-S6643428
FT-127-C30	FT-364-FH-025	FT-S6224511,12	FT-S6643528
FT-127-CO30	FT-364-FH-035	FT-S6224611,12	FT-S7117428
FT-140-F-0428	FT-364-FHA-045	FT-S6224711,12	FT-S7117728
FT-140-F-0628	FT-364-FHA-055	FT-S6225011,12	FT-S7444722
FT-140-F-0828	FT-364-FHA-065	FT-S6225111,12	FT-S7445522
FT-140-F-1028	FT-364-FHA-075	FT-S6225211,12	FT-S7446022
FT-140-F-1228	FT-364-FHA-085	FT-S6225311,12	FT-S7446222
FT-140-F-1428	FT-364-FHA-105	FT-S6225411,12	FT-S748332
FT-140-F-1828	FT-364-FHA-125	FT-S6225511,12,13	FT-S750151,2
FT-140-F-2228	FT-364-FHA-145	FT-S6225711,12	FT-S750461.2
FT-140-F-2628	FT-364-FHA-165	FT-S6225811,12	FT-S7553124
FT-142-F28	FT-364-FHAM-10MM5	FT-S6226011,12	FT-S766371
FT-163-F8	FT-364-FHAM-12MM5	FT-S6226111,12	FT-S776154
FT-174-F2	FT-364-FHAM-6MM5	FT-S6226211,12	FT-S81156014
FT-193-S24	FT-364-FHAM-8MM5	FT-S6226311,12	FT-S869440123
FT-194-S25	FT-364-FHB-046	FT-S6226411,12	FT-S877130123
FT-195-FB18	FT-364-FHB-056	FT-S6226511,12	FT-S877170123
FT-195-FC15	FT-364-FHB-066	FT-S6226611,12	FT-S877180123
FT-195-SA24	FT-364-FHB-076	FT-S6226811,12	FT-S891160123
FT-2000-FS27	FT-364-FHB-086	FT-S6226911,12	FT-TC-10001
FT-201-F 8	FT-364-FHBM-10MM6	FT-S6227511,12	FT-TC-10201
FT-203-FA15	FT-364-FHBM-12MM6	FT-S6227611,12	FT-TC-10501
FT-206-FB2	FT-364-FHBM-6MM6	FT-S6227711,12	FT-TC-20501
FT-208-F28	FT-364-FHBM-8MM6	FT-S6227811,12	
FT-208-FSS28	FT-367-FH8	FT-S6227911,12	
FT-227-FA2	FT-368-FH8	FT-S6228011,12	
FT-260-FHA9	FT-375-FS15	FT-S6228111,12	
FT-270-F-0610,12	FT-376-FS15	FT-S6228211,12	
FT-270-F-0810,12	FT-384-FA3	FT-S6228311,12	
FT-270-F-1010,12	FT-395-FAM15	FT-S6228411,12	
FT-270-F-1210,12	FT-400-F20	FT-S6228511,12	
FT-270-F-1410,13	FT-401-FA20	FT-S6228711,13	
FT-270-F-1610,13	FT-402-FA20	FT-S6228811,12,13	
FT-270-F-1810,13	FT-406-FA2	FT-S6229011,13	
FT-275-FS25	FT-407-F22	FT-S6229111,12,13	
FT-275-FSC27	FT-407-FA22	FT-S6229211,12,13	
FT-278-FS-03X04X0625	FT-437-FB19	FT-S6229411,12,13	
FT-278-FS-0525	FT-447-F21	FT-S6229511,12,13	
FT-278-FS-0825	FT-500-FC16	FT-S6229611,12,13	
FT-278-FS-1025	FT-500-FCM16	FT-S6229711,12,13	
FT-278-FS-1225	FT-507-FB19	FT-S6229811,12,13	
FT-278-FS-1425	FT-507-FBM19	FT-S6229911,13	
FT-278-FSM-0825	FT-525-F17	FT-S6230011,13	
FT-278-FSM-1225	FT-537-F21	FT-S6230111,13	
. 1 LIO I OM 1220	1100/11	1 1 002001	

## **Tubing Tool Selector**

				Tube Material						
				Copper						1
			Annealed	_	Type K		Type L			_
Tool	Part No.	Size Range Tube O.D.	General Purpose	Soft	Bending Temper-Hard	Hard	Soft	Bending Temper-Hard	Hard	Тур
Tube Cutters	TC 1050	1/8-5/8	Purpose	0	0	•				
Metal Tubing	TC 2050	3/16-7/8				:	:	:	:	
	174-F 206-FB	3/8-1 1/8 3/8-2 5/8								
	227-FA	1/8-3/4				:	:	:	:	
	TC 1000 312-FC	1/8-1 1/8 1/8-5/8		:						
	406-FA	1/8-5/8	•	•	•	•	•			
Tube Cutters Thermoplastic	307-FP 327-FP	1/16-1/2 4) 1/8-13/16 4)								
Rubber Hose	384-FA	1/8-1 1/2			•		0	•		
Bending Tools	101-F 102-F	1/4-5/8 1/4-3/4								
	102-F 112-F	1/4-3/8								
	163-F	1/4-5/8								
	260-FHA 270-F	1/4-7/8 3/8-1 1/8		:	1			1		
	350-FHA	1/4-3/4								
	364-FH 364-FHA	1/8-3/16 1/4-1		:			0			
	364-FHB	1/4-1/2								
	364-FHBM 367-FH	6-12mm 1/8,3/16,1/4		:			:			
	368-FH	1/4.5/16.3/8								
	564-FH	3/8,1/2			•		:	•	•	
	600-F 700-F	1/4-3/4 1/4-3/4		8			ě			
37° Flaring Tool	400-F	3/16-5/8						•		2
	407-FA	1/8-1 1/2 3/16-5/8	2		:	:	:			3
	437-FB 447-F	1/8-1/2			0	•				2
	507-FB 555-FS	3/16-5/8 3/16-5/8		:	:	:	0			200
	537-F	3/4-1 1/4			0					Ž
	637-F	1 1/4-2	0		:	:	8			2
45° Flaring Tool	2000-FS 103-FS	3/4-1		•		•	0			000000000000000000000000000000000000000
45 Flaring Tool	195-FC	3/16-5/8	•		•					2
	203-FA 275-FS	5/8-1 1/8 1/8-3/4	0 0 0 0 0 0	:	:	:				8
	296-FC	3/16-5/8			ě	_				Ž
	300-FB	3/16-5/8						•		2
	375-FS 376-FS	1/8-3/4 1/2-3/4		:	· ·	:	ě		000	2
	395-FAM	4-16mm								2
	500-FC 500-FCM	3/16-5/8 6-16mm		:	:	:	:		:	8
	525-F	3/16-5/8			0					2
	555-FS	4, 7-16mm 3/16-5/8	:	:		:	:		•	9999
	2000-FS	1/8-3/4		ě	ě	ě		ė		2
45° Double	93-FB	3/16-1/2								
Flaring Tools	195-FB 2000-FS	1/4-3/4 3/16-3/4					ě			
Reaming and	208-F	3/16-1 1/2	0	•		•	0			
Deburring Tools	208-FSS	3/16-1 1/2	0			•	0		0	
Tube Constrictor Swaging Tools	TC 1020 93-S	1/8-1 1/8 3/16-7/8	0	•			0			
Chaging 100is	94-S 193-S	1/2,5/8,7/8								
	193-S 194-S	1/2,5/8,7/8 1/4-5/8 1/2-7/8	0	:						
	195-SA	1/4-5/8	ě				ě			
	275-FS	3/16-3/4	0 0	:			0			0
	555-FS 2000-FS	3/16-5/8 3/16-3/4	i i	:						
Metric Bubble	293-F	4.75-10mm								
Flaring Tool										